



access units
MOTION 868 MHz range

Applicable to doors
roller · sliding · swing · fast · glass

FreeTH









hands-free system for people
management



jcmtechnologies
be a step ahead with technology and imagination



FreeTH · Free15r · Free30r · Free50r

<p>TAG</p>  <p>FreeTH</p> <ul style="list-style-type: none"> · Nominal range 100 metres. · Transmission frequency 868 KHz. · Power: CR2032-type 3Vdc battery. · Batteries last for approximately 2 years. · LED operating indicator for low battery, signal transmission and programming · Operating temperature -20°C a + 55°C. · PC IP66 plastic case. · Size: 48 x 48 x 12 mm. 	<p>ACCESSORIES</p>  <p>FreeTHP FreeTH with single-use water-resistant plastic bracelet.</p>  <p>FreeTHT FreeTH with reusable water-resistant fabric bracelet</p>
<p>ANTENNA</p>  <p>Free15r · Free30r</p> <ul style="list-style-type: none"> · Free15r nominal range: 1.5 metres. · Free30r nominal range: 3 metres. · Transmission frequency: 125 KHz. · Power: 12/24Vac/dc. · LED operations indicator. · Button input for channel and/or group programming · Pre-wired connection. · Operating temperature -20°C a + 55°C. · ABS IP66 plastic case. · Size of Free30r: 205 x 183 x 14 mm. · Size of Free15r: 87 x 78 x 15 mm.  <p>Free50r</p> <ul style="list-style-type: none"> · Triggers with activation input · Free50r nominal range: 5 metres. · Transmission frequency: 125 KHz. · Power: 230Vac. · LED operations indicator. · Button input for channel and/or group programming. · Pre-wired connection. · Operating temperature -20°C a + 55°C. · ABS IP66 plastic case. · Size of Free50r: 394,4 x 310,5 x 41,6 mm. 	 <p>Wall support Free30r, Free50r y Free50rs.</p>  <p>Wall support Free50r</p>
<p>RECEIVERS</p> <p>Receivers MOTION. BASE, WAVE, STICK, CONNECT, ACCESS500, ACCESS1000 and operating panels with built-in receiver.</p>	



GROUP CONCEPT

